

Chlor-Away®

Dechlorination Tablets

Chlor-Away sodium sulfite tablets are formulated to be readily soluble in water and are a powerful dechlorination product for residential, municipal and industrial applications:

- Water line flushing/Hydrostatic testing
- Wastewater
- Process water
- Cooling tower blowdown
- Boiler water
- Pool and spa backwash

Chlor-Away Dechlorination Tablets:

- Contain one of the strongest blends of sodium sulfite available in tablet form
- Are 2 5/8" and fit into most standard tablet feeder systems
- Contain a minimum of 85% sodium sulfite
- Provide a slow, steady and consistent sulfite dose
- Are designed with a smaller, beveled-edge to minimize wicking
- Dechlorinate - removing residual chlorine prior to discharge
- Help meet National Pollutant Discharge Elimination System (NPDES) permit requirements and The Clean Water Act
- Require no mixing of chemicals or solutions
- Minimize storage space with convenient, stackable pails



Residential/Municipal/Industrial Suggested Dosage Rates:

Application	Residual	Dosage
Water line flushing/Hydrostatic testing	50,000 GPD at 50 ppm	139 tablets per day
Wastewater	10,000 GPD at 2 ppm	1 tablet per day
Process water	10,000 GPD at 2 ppm	1 tablet per day
Cooling tower blowdown	50,000 GPD at 2 ppm	5 1/2 tablets per day
Boiler water	50,000 GPD at 2 ppm	5 1/2 tablets per day
Pool and spa backwash	10,000 GPD at 2 ppm	1 tablet per day

*Additional dosage guidelines can be found on the product label

Solution Reference Guide

$[(\text{chlorine to be removed in mg/L} \times 1.775) / .85] \times \text{plant flow in liters per day} / 1,000/140 = \text{quantity of tablets required per day}$

Note: Suggested dosage rates are for estimation purposes and in no way guarantee actual usage rates. Many factors other than flow rate can contribute to chemical usage rates such as pH, turbidity, water temperature, etc.

Available in 45 lb pails